








Heavy Duty Temperature Probes

type K thermocouple

	order code	
<p>penetration probe</p>  <p>Ø4 x 100 mm</p>	<p>This robust, stainless steel penetration probe incorporates a T-shaped polypropylene handle and is ideal for a variety of heavy duty applications including food processing and other similar industries.</p> <ul style="list-style-type: none"> • response time less than 4 seconds • probe temperature range -75 to 250 °C 	133-124
<p>reduced tip probe</p>  <p>Ø6.35 x 100 mm</p>	<p>This robust, stainless steel, reinforced needle probe incorporates a T-shaped polypropylene handle and a reduced sensing tip for faster response. Ideal for a variety of heavy duty applications including food processing etc.</p> <ul style="list-style-type: none"> • response time less than 9 seconds • probe temperature range -75 to 250 °C 	133-126
<p>reduced tip probe</p>  <p>Ø6.35 x 300 mm</p>	<p>This extended robust, stainless steel, reinforced needle probe incorporates a T-shaped polypropylene handle and a reduced sensing tip for faster response. Ideal for a variety of heavy duty applications including food processing etc.</p> <ul style="list-style-type: none"> • response time less than 9 seconds • probe temperature range -75 to 250 °C 	133-120
<p>reduced tip probe</p>  <p>Ø8 x 500 mm</p>	<p>This extended, stainless steel, reinforced needle probe incorporates a T-shaped polypropylene handle and a reduced sensing tip for faster response. Ideal for a variety of heavy duty applications including food processing etc.</p> <ul style="list-style-type: none"> • response time less than 10 seconds • probe temperature range -75 to 250 °C 	133-130
<p>reduced tip probe</p>  <p>Ø9.5 x 1000 or 1400 mm</p>	<p>This Ø9.5 mm stainless steel, reinforced needle probe incorporates a T-shaped polypropylene handle and a reduced sensing tip for faster response. Ideal for applications where a longer probe is required, i.e. grain silos.</p> <ul style="list-style-type: none"> • response time less than 17 seconds • probe temperature range -75 to 250 °C 	133-136 (1000 mm) 133-135 (1400 mm)
<p>reduced tip probe</p>  <p>Ø9.5 x 2000 mm</p>	<p>This extended stainless steel, reinforced needle probe incorporates a T-shaped polypropylene handle and a reduced sensing tip for faster response. Ideal for applications where a very long probe is required, i.e. grain silos.</p> <ul style="list-style-type: none"> • response time less than 17 seconds • probe temperature range -75 to 250 °C 	133-133
<p>corkscrew probe</p>  <p>Ø8 x 100 mm</p>	<p>This stainless steel probe incorporates a heavy duty T-shaped polypropylene handle and a corkscrew design sensing tip. Ideal for industrial and food processing applications. Supplied with a one metre PVC detachable lead.</p> <ul style="list-style-type: none"> • response time less than 9 seconds • probe temperature range -75 to 250 °C 	133-175

Please note: for hand held type T thermocouple probes, replace the third digit (3) of the order code with the number 7

